



Designers and Manufacturers
of Custom Adhesive Application and Automatic Spraying Equipment
electromatic automatic airless spray and extrusion equipment
thermopulse hot melt and cold adhesive systems
compuspray automatic test panel spray units

CE Declaration of Conformity

We Spraymation Inc. declare that the industrial equipment products listed below:

306899 Stainless Steel ASME Pressure Tank, 5 gallon (20 liter), 35 PSI (2.4 Bar) maximum with ASME Relief valve, low level switch, and programmable pressure switch.

See GR 306899 for full description, installation and operating instructions.

Conforms to the following standards, directives or publications:

Standard	Date	Standard Title
EN-60204-1	2006	Electrical Equipment of industrial Machines
2006/95/EC	2006	Low Voltage Directive
2006/42/EC	2006	Machinery Directive
97/23/EC	1997	Pressure Tank Directive

All electrical components operate on low voltage and are EXEMPT.

The pressure tank is 5 gallons, nominal (20L) and has a safety relief valve to limit pressure to 35 PSI (2.4 Bar) this combination give a pressure volume product of 48 Bar-Liters which is under the 50 Bar-Liter pressure tank requirement and is EXEMPT from the Pressure Tank Directive for Group 2 fluids.

Spraymation is registered ISO9001:2008 by LGA, certificate #QM_192774 that expires on 1/12/2016.

CE mark is displayed on this item.

Design and Safety data are complete for this item, have been reviewed, are current, and conform to the standards and details listed above. The manufacturing and testing documents support and will maintain the indented design and quality.

Approved David Kerzel
Title Chief Engineer
Date Approved May 7, 2015

This CE Declaration of Conformity may be used with new items until May 7, 2020 when the design, safety data, standards and directives must be reviewed.